

NASSIMI

Nassimi LLC
370 Seventh Avenue
Suite 1700
New York, NY 10001

T 212.643.8080
T 800.521.5208
F 212.643.2626
W www.nassimi.com

Product Specification Sheet

Pattern: Decora

Date: 06/20/2011

THE SYMPHONY COLLECTION

General Specifications

Weight (linear yard)	29.0 oz
Width	54 "
Thickness	1.20 mm
Gauge	0.048
Emboss	Decora
Surface Composition	PVC
Substrate Composition	Polyester
Substrate Weight	5.12 oz

General Treatments

UV Resistance	500 Hours	CFFA-2 / ASTM G26-96 Method C
Cold Crack	-20 F	CFFA-6 Federal Standard No. 191A-Method 5874
Mildew Resistant	Pass	CFFA-120 / ASTM G21-96
Anti-Bacterial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Anti-Microbial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Resilience SR	Yes	
Bleach Resistant	Yes	Diluted 1:10

Physical Strength Properties

Abrasion	100,000 Cycles		CFFA-1A/ Method ASTM D 4157-92
Adhesion	N/A Warp	N/A Fill	CFFA 3/ ASTM D751-98
Tear Strength	22.3 Warp	15.5 Fill	CFFA-16/ ASTM 5733-95
Tensile Strength & Elongation	112 Warp	71 Fill	CFFA-17/ ASTM D751-98
Seam Strength	N/A Warp	N/A Fill	CFFA-14/Method ASTM D751-98
Stretch and Set	N/A Warp	N/A Fill	CFFA-15/SAE Method J-855

Flame Retardancy Standards

California Technical Bulletin 117	Pass	NFPA 260	Pass
UFAC Class I	Pass	Boston Fire Code (BFD IX-1)	Pass
BIFMA CS-191-53, Section 3	Pass	IMO A.652(16)8.2	Pass
BIFMA Upholstery, Section 4	Pass	ASTM E84: Class I or A Rating	N/A
MVSS 302	Pass		