

DECORA Specifications

GENERAL SPECIFICATIONS

Width	54"
Roll Size	30 Yards
Weight	29 Ounces per Linear Yard
Backing	100% Brushed Polyester Knit

PERFORMANCE SPECIFICATIONS

Abrasion Resistance	100,000+ Double Rubs per ASTM D 4157-92 Wyzenbeek / CFFA-1A
Mildew Resistant	ASTM G21-96 / CFFA-120
Anti Bacterial	AATCC 147 / CFFA300
Anti Microbial	ASTM G21 / CFFA 120
Ultra Violet Resistant	500 Hours ASTM G26-96 Method C / CFFA-2
Cold Crack	-20° F Federal Standard No. 191A-Method 5874 / CFFA-6
Stain Resistant	Resilience ^{SR} Protection
Sulfide Stain Resistant	

FLAMMABILITY REQUIREMENTS

California Fire Code Technical Bulletin No. 117, Section E
BIFMA
UFAC Class 1
MVSS 302
NFPA 260
IMO A.652 (16) 8.2
IMO A.652 (16) 8.3
May Comply with California 133 when Tested with Suitable Components
Can be Treated to Pass FAA 25.853

Resilience^{SR} represents the latest technology in Faux Leather and Vinyl Protection, enhancing performance where it is needed the most:

Stain Resistance: With proper care, materials treated with Resilience^{SR} can be easily cleaned and will guard against stains maintaining the desired surface appearance for years to come.

Anti-Microbial & Anti-Bacterial Protection: Products treated with Resilience^{SR} are engineered to inhibit bacterial growth, as well as fungus, mold and mildew spores, resulting in a more hygienic environment.

Abrasion Resistance: Resilience^{SR} provides additional wear properties and surface durability to any Vinyl or Faux Leather, thereby increasing the life of the material.

Resilience^{SR} is not visible, and does not affect the hand of the material. Resilience^{SR} is engineered to last, even after repeated cleaning and wear. Specify Resilience^{SR} for the most demanding healthcare and hospitality applications.