

# ULTRA Specifications

---

## GENERAL SPECIFICATIONS

<b>Width</b>	54"
<b>Roll Size</b>	30 Yards
<b>Weight</b>	17/18 Ounces per Linear Yard
<b>Surface</b>	100 % Polyurethane
<b>Backing</b>	High Twist Polyester / Rayon

## PERFORMANCE SPECIFICATIONS

<b>Abrasion Resistance</b>	100,000+ Double Rubs per ASTM D 4157-92 Wyzenbeek / CFFA-1A
<b>Ultra Violet Resistant</b>	500 Hours ASTM G26-96 Method C / CFFA-2
<b>Cold Crack</b>	-20° F Federal Standard No. 191A-Method 5874 / CFFA-6
<b>Stain Resistance</b> (per AATCC 130)	<b>Coffee:</b> Class 5.0 <b>Blood:</b> Class 5.0 <b>Urine:</b> Class 5.0 <b>Betadine:</b> Class 4.5 <b>Cola:</b> Class 5.0 <b>Ketchup:</b> Class 5.0

Grading: Class 5 - Excellent; Class 4 - Good, Class 3 - Fair, Class 2 - Poor, Class 1 - Very Poor  
The information above refers to performance in tests conducted under laboratory conditions.  
Results may vary under actual conditions.

## FLAMMABILITY REQUIREMENTS

California Fire Code Technical Bulletin No. 117, Section E

BIFMA

UFAC Class 1

MVSS 302

NFPA 260

IMO A.652 (16) 8.2

ASTM E84

May Comply with California 133 when Tested with Suitable Components